

Masonry Wall System with Superior Resistance to Moisture Penetration

Innovative Masonry Design

- WCT units feature integral drainage zones that direct moisture to the wall's drainage system.
- No special installation techniques required--cost-effectiveness is assured.
- WCT units are suitable for corners and ends for a complete system.
- All units have integral water repellent in their mix design.
- WCT units meet or exceed ASTM C90.
- Perfect for both Single or Multi-Wythe Walls.
- Offered in a wide variety of shapes and sizes, ranging from:
 - SPEC-BLOCK[™] (precision gray CMU)
 - SPEC-BRIK® (brick appearance),
 - SPEC-SPLIT[™] (split face CMU)





WCT units (on left) were spray bar tested with no mortar (just gaps) alongside a traditional block design (right) with a water flow rate equivalent to 180" of rain per hour for a half hour and then at a rate of 30" of rain for an additional 24 hours.

Result: The traditional block began to show moisture penetration to the interior surface after 11 seconds. The WCT block completed the 24 hour test without any evident moisture penetration to the interior surface of the wall.



U.S Patents Nos.: 9,068,342 B2, D673,302 S, D673,304 S

How does WCT[™] Work?


Why try to improve one of the most trusted construction materials available?

WCT is based on preserving the superior performance characteristics of concrete block while adding features that improve the ability of masonry wall assemblies to resist moisture penetration.

We made subtle changes to the top surfaces of each WCT block's webs to discourage water from crossing to the interior face shell. Corners and ends can use the WCT drainage zones without compromising aesthetics or performance.

These innovations are accomplished with a block that is fully compliant with the concrete masonry unit standard, ASTM C90.

Views below show the interior cores of WCT™ vs. Standard CMU under extreme (180 inch/hour) spray bar testing:






Exterior - Spray Bar Side

WCT drainage
features divert
water downward to
weeps/drainage

Interior of Wall

WCT™ CMU

The WCT drainage zones divert water from traveling across joint areas and direct any moisture that penetrates the exterior shell downward into the drainage cores of the units so that the water can exit via the flashing and weep systems in the wall



Available Nationwide



The Concrete Products Group LLC (CPG) consists of 14 regional market leaders in the concrete products industry. CPG is organized to provide consistent, top-quality products to regional and national customers. Our products are produced with consistent specifications and production expertise.



A-1 BLOCK 1617 South Division Avenue Orlando, FL 32805 AMCON CONCRETE PRODUCTS, LLC 2025 Centre Pointe Blvd., Suite 300 Mendota Heights, MN 55120-1221

P.O. Box 280 5894 Court St. Rd. Syracuse, NY 13206-0280

BARNES & CONE

BARRASSO AND SONS INC 160 Floral Park Street Islip Terrace, NY 11752 BASALITE CONCRETE PRODUCTS LLC 605 Industrial Way Dixon, CA 95620

DAGOSTINO BUILDING BLOCKS, INC. 1111 Altamont Avenue Schenectady, NY 12303 FENDT BUILDERS SUPPLY 22005 Gill Rd, Farmington, MI 48335

FIZZANO BROTHERS CONCRETE PRODUCTS, INC. 1776 Chester Pike Crum Lynne, PA 19022-1299 JANDRIS BLOCK 202 High St. Gardner, MA 01440 JOHNSON CONCRETE COMPANY 217 Klumac Road Salisbury, NC 28144 LEE BUILDING PRODUCTS 4301 Industrial Drive Bowling Green, KY 42101 ORCO BLOCK & HARDSCAPE 11100 Beach Blvd. Stanton, CA 90680-0129 TEXAS BUILDING PRODUCTS 3261 Highway 108 Strawn, Texas 76454 WESTERN MATERIALS COMPANY 1202 South First Street Yakima, WA 98901